



GOLDEN STALLION

www.usglobalpetroleum.com 773-376-9660

SAE-90 GL-4 Gear Oil

Golden Stallion SAE-90 GL-4 Gear Oil is a multi-purpose lubricant blended from selected high viscosity base stocks and advanced additives. Golden Stallion GL-4 Gear Oils provide superior extreme pressure, oxidation stability, rust, corrosion, anti-wear, anti-scuff and anti-foam protection. They are recommended for use in automobile, truck and heavy equipment gear boxes, manual transmissions, bearings, gear reducers and many other applications where an API service classification GL-4 gear oil is specified.

Benefits and Applications

- Reliable film strength for wear protection
- First-rate oxidation and foam resistance
- Good seal protection and lubricant life
- Superior extreme pressure, oxidation stability and anti-foam protection
- Excellent rust, corrosion and anti-wear protection

Typical Characteristic SAE-90 Gear Oil

| SAE GRADE | | SAE-90 |
|------------------------|-------------|-------------|
| Performance Level | | GL-4, MT-1 |
| API Gravity | ASTM D287 | 27.13 |
| Flash Point, COC °C/°F | ASTM D92 | 230 / 446 |
| Pour Point, °C/°F | ASTM D97 | -33 / -27.4 |
| Viscosity @ 40°C, cSt | ASTM D445 | 161 |
| Viscosity @ 100°C, cSt | ASTM D445 | 15.5 |
| Viscosity Index | ASTM D2270 | 95 |
| Demulsibility | ASTM D14016 | Pass |

Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

API GL-4 / MT-1



V200330

HANDLING AND SAFETY INFORMATION - Refer to GOLDEN STALLION (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.